



## Greater opportunities for small businesses - Slican IPM-032

Do you run a small business? Do you care for technologically advanced telecommunications solutions? We have the solution for you - SLICAN IP PBX IPM-032. Due to the uniform, advanced IT platform, provides a cheap VoIP communication right from the basic product version. IP PBX IPM-032 is a universal system, that will grow with your company.

Telephone exchanges IPM-032 are characterized by flexibility modular structure. Whole system is extended by its own and external applications, creating a complete safe system of cheaper and telecommunications for success oriented companies.















IPM-032.WM

IPM-032.2U



IP PBX IPM-032 is CTIP, XML, HTTP, HOTELP, TAPI and EdbRECP protocol. It allows you integration with variety of other applications, where the added value is a professional software deployment without incurring the additional investment costs. Slican CTI Communicator is a set of intuitive solutions on computers and smartphones. Slican TAPI – Slican PBX-es cooperating with MS Outlook® application. Due integration, the client can use unified communications, combining phone and mail.



IP PBX IPM-032 will allow your company flexible expansion of the telecommunications system. Networking with other Slican IP PBX-es up to 3999 subscribers enables almost unlimited configuration of telecommunications system according to the needs of your business.



## COST CONTROL

Online support allow you to apply cost saving policy for your company, associated with programming and PBX service. LCR (Least Cost Routing) solution, billing applications, ensure the lowest bills and cost control.



### WORK ORGANIZATION

Slican RecordMAN application suite provides professional business record and management of calls. Using the teleconference provides better organization of work within the company. INVENIO Infolines provide flexible navigation that will help callers a fast connection to the department of the company.





# Greater opportunities for small businesses - Slican IPM-032

		IPM-032.A6x4.WM	IPM-032.L6x4.WM	IPM-032.A8x4.2U	IPM-032.L8x4.2U
Maximal capacity	Analogue ports AB (FXS)	24	24	32	32
	Analogue trunks POTS (FXO)	12	12	16	16
	ISDN BRA (int. or ext.)	12	12	16	16
	E 1 / ISDN PRA (int. or ext.)	2		2	
	IP channels	8 / 64	4	8 / 64	4
	IP trunks (SIP)	100	8	100	8
	IP subscribers (SIP)	1000	8	1000	8
	GSM trunks	12	12	16	16
	CTS system ports (Up <sub>0</sub> + IP)	124	10	124	10
	Calls recording channels	12	4	12	4
	SD memory cards	1	1	1	1
Available devices		Slican system phones CTS Up <sub>0</sub> / IP CTS-102, CTS-202**, CTS-203 and CTS-330*** series			
		Slican SIP phones VPS-2000P, VPS-804P, VPS-802			
		Slican analog phones XL-2023ID and XL-209			
		hot line Slican phone HLP-22			
		Slican consoles CTS-232 and CTS-338			
		Slican DPH series door phones			
		Multi Switch Box (MSB-1102) and Multi Audio Box (MAB-1101)			
Applications supporting IPM-032		Slican CTI Communicator - PhoneCTI, MobileCTI and WebCTI			
		Slican BillingMAN / BillingMAN.plus			
		Slican RecordMAN.server / RecordMAN.client			
VoIP parameters	Supported protocols	eSSL*, SIP 2.0 codes G.711 - standard, G.729* and G.711μ* - option			
	Working mode	VoIP master or / and slave			
Protocols	Voice communication protocols	POTS / ISDN-EDSS1 / QSIG / SIP 2.0 / GSM900 / 1800 / 1900 / Up <sub>0</sub>			
	Server communication protocols	CTIP / HOTELP / TAPI / EbdRECP / HTTP / XML			
Power supply		~110-230V;50- 60 Hz; < 150 VA	~110-230V;50- 60 Hz; < 150 VA	~110-230V;50- 60 Hz; < 150 VA	~110-230V;50-60 Hz; < 150 VA
Buffer power supply		option	-	option	-

<sup>\*</sup>excluding IPM-032.L6x4.WM and IPM-032.L8x4.2U

The presented material is for information purposes. In order to properly configure of PBX, we recommend contact and consultation with Slican Distributor / Reseller.

<sup>\*\*</sup>Slican CTS-202.IP system phone does not work with the CXS-0424, CCT-1668 and MAC-6400 PBX with 6.01 firmware and higher and with IPx series PBXes

<sup>\*\*\*</sup> Slican CTS-330.IP need PBX firmware v. 6.20 or higher, Slican CTS-330.CLBT and CTS-330.IPBT need PBX firmware v. 6.30.0060 or higher